



Supply air louvre ACOUSTIC 7010 / 7020

Technical specifications | Material specification | Accessories | Installation details | References



Technical Specifications

width of the single unit: 300 - 2000 mm

height of the single unit: 440 - 3000 mm

depth of louver:

- type 7010: 305 mm
- type 7020: 610 mm
- Inherently stable aluminum construction with inserted, acoustically lined slats
- Fin: streamlined design
- Fixed execution

Material Specifications

- grille with inset of corrosion-resistant Aluminum fins of the alloy AlMg3
- minimum thickness of 1.5 mm
- perforated sheets of aluminum RV5 / 8
- fasteners: aluminum or stainless steel

Accessories (optional)

- Stainless steel
- Powder coating 80 µm in RAL finish
- Anodized
- Bird screen: aluminium / stainless steel / galvanized steel
- Insect screen: stainless steel / plastic

No. Blades	Height (mm)
2	440
3	590
4	740
5	890
6	1040
7	1190
8	1340
9	1490
10	1640
11	1790
12	1940
13	2090
14	2240
15	2390
16	2540
17	2690
18	2840
19	2990
20	3140
21	3290

Frequency	(Hz)	63	125	250	500	1K	2K	4K
Type 7010	(dB)	3.2	4.8	6.5	11.8	17.5	20.7	19.5
Type 7020	(dB)	6.1	7.8	10.7	19.8	30.1	30.9	29.4



